

Dynaflow SCH / DSCH Fume Cupboards

Company Profile

Dynaflow is an Australian based company specialising in laboratory fume risk control. We design, manufacture, install, and maintain fume cupboards, fume scrubbers, and specialised ventilation systems for laboratory applications.



^{*} Dynaflow fume cupboards are fully compliant to AS/NZS 2243.8 standard and is the only Australian fume cupboard with Third Party Product Certification by SAI Global.



Our company has Third Party Accreditation with NATA.

Our company has Third Party Accreditation with SAI Global for ISO9001 Quality Management Systems.

We have a strong network of support with offices in Sydney, Melbourne, Adelaide, Perth and distributors in various regions of the world. With over 30 years of product history in Australia and over 40 countries around the world, we have completed thousands of Special Application projects in key industries spanning Research, Teaching, Mining, Refinery and Pharmaceutical.

"Nothing Left to Chance"

Email: info@dynaflow.com.au Website: www.dynaflow.com.au

Dynaflow Pty Ltd ABN 28 008 493 178

CONTACT

Sydney Head Office 30 Waratah St, Melrose Park NSW Locked Bag 801, Ermington 1700 Australia Tel: +61 (0) 2 9858 0190 Fax: +61 (0) 2 9858 1100

Application

- Suitable for SCHOOLS Science laboratories
- Double sided model is ideal for locations between Prep room and Classroom

• Also suitable for light chemistry process laboratories

Product Data

- Full Compliance to AS2243.8
- Available in Single Sided or Double Sided
- Available in 1000, 1200, 1500, 1800 mm wide sizes
- Body construction is available in Single Skin White uPVC, or Toughened Glass on sides
- Single one piece High Pressure Laminates worktop (Trespa® or Labolam®)
- Dynasafe MK-5 Control Panel and mimic panel for Double Sided option

Range of Dynaflow Products and Services

- Dynaflow SCH / DSCH Fume Cupboards (AS2243.8)
- Dynaflow GRP Fume Cupboards (AS2243.8)
- Dynaflow Recirculating Fume Cupboards (AS2243.9)
- Dynaflow WALKIN Fume Cupboards (AS2243.8)
- Dynaflow Fume Scrubbers and Exhaust Systems
- Dynaflow Explosion-Resistant Fume Cupboards (AS2243.8)
- Dynaflow Disabled Access Fume Cupboards (AS2243.8)
- Slotted Wall Hood and Fixed Hood Exhaust Systems
- Dynawaste Acid Neutralising Waste Systems
- Managed service contracts, web based compliance viewer and user training in correct use of fume cupboard systems
- Safety compliance upgrades on existing fume cupboard systems
- Energy conservation features and upgrades on fume cupboard systems
- Laboratory Extraction Arms (third party supplier)
- Storage cabinets complete with ducted vent systems

Adelaide Office

Unit 2, 6-8 William St Norwood SA 5027 Australia Tel: +61 (0) 8 8332 4477 Fax: +61 (0) 8 8332 4488 Perth Office

Unit 2, 16 Tacoma Circuit Canning Vale WA 6155 Australia Tel: +61 (0) 8 9256 4600 Fax: +61 (0) 8 9256 4699

Dynaflow

Syncroflow

Melbourne Office

Unit 15, 20 Duerdin St

Tel: +61 (0) 3 9558 6700

Fax: +61 (0) 3 9558 6722

Clayton North VIC 3168 Australia

Dynasafe

Cleanflow





Dynaflow SCH / DSCH Fume Cupboards

Model	Dynaflow	Dynaflow	Dynaflow	Dynaflow
inouci	1000SCH / DSCH	1200SCH / DSCH	1500SCH / DSCH	1800SCH / DSCH
External Sizes (mm)	1000 x 750 x 1550	1200 x 750 x 1550	1500 x 750 x 1550	1800 x 750 x 1550
Design Face velocity	0.5 meters / sec			
Maximum Air Qty at Design velocity	280 Litres / Sec	345 Litres / Sec	445 Litres / Sec	540 Litres / Sec
Variable Volume (sash Fully Open)	280 Litres / Sec	345 Litres / Sec	445 Litres / Sec	540 Litres / Sec
Variable Volume (sash Open 250 mm – working height)	107 Litres / Sec	132 Litres / Sec	171 Litres / Sec	207 Litres / Sec
Variable Volume (sash Fully Closed)	45 Litres / Sec	55 Litres / Sec	70 Litres / Sec	85 Litres / Sec
Worktop Material	High Pressure Laminate LABOLAM® (Std) – Optional TRESPA®, Stainless Steel, Epoxy, Ceramic			
Available Work Area (mm)	980 x 720	1180 x 720	1480 x 720	1780 x 720
Construction Design	Single Skin Type			
Chamber Material	6 mm PVC or 6 mm Toughened Glass			
Aerodynamic Front Facia Material	One Piece Moulded GRP Aerodynamic Design			
Sash Material	6 mm Toughened Glass			
Recommended Duct Outlet Size <i>(mm)</i>	250ø	250ø	315ø	315ø
Operator Control Panel	Dynasafe MK-5 Control System (plus mimic panel for Double-Sided systems)			
Internal Pre-wiring	Fully Pre-wired			
Power Supplies	240V Single Phase (Std) – Optional as necessary for various countries			
Services Options (Double-Sided fume cupboards have dual controls)				
Extra Sinks in worktop	100ø or 150ø Pot sink RHS/LHS or Both (Other sizes available)			
Water Services	Cold water, Hot Water, RO Water, Mixer			
Dry Services	Town Gas, Nitrogen, Compressed Air, Vacuum, Argon and various others available			
Power Points	10 Amp Double, 15 Amp Single and Other special types available			



Sydney Head Office 30 Waratah St, Melrose Park NSW

Locked Bag 801, Ermington 1700 Australia Tel: +61 (0) 2 9858 0190 Fax: +61 (0) 2 9858 1100
 Melbourne Office

 Unit 15, 20 Duerdin St

 Clayton North VIC 3168 Australia

 Tel: +61 (0) 3 9558 6700

 Fax: +61 (0) 3 9558 6722

Adelaide Office Unit 2, 6-8 William St Norwood SA 5027 Australia Tel: +61 (0) 8 8332 4477 Fax: +61 (0) 8 8332 4488 Perth Office

Unit 2, 16 Tacoma Circuit Canning Vale WA 6155 Australia Tel: +61 (0) 8 9256 4600 Fax: +61 (0) 8 9256 4699

Dynaflow

Syncroflow

Dynasafe

Cleanflow

Pifan